

Flexible RF cable

RG_142_B/U Item: 22510037

Description

RG: RG type RF cables

RG142, 50 Ohm, 6 GHz, 200°C, ø4.95 mm, FEP jacket



Technical Data

Construction

| | Material | Detail | Diameter |
|------------------|--------------------------------------|---------------|-----------------|
| Centre conductor | Steel, Copper+Silver plated | Wire | 0.95 mm |
| Dielectric | PTFE (Polytetrafluoroethylene) | | 2.95 mm |
| Outer conductor | Copper, Silver plated | Braid, 97% | 3.6 mm |
| Outer conductor | Copper, Silver plated | Braid, 94 % | 4.25 mm |
| Jacket | FEP (Fluorinated ethylene propylene) | RAL 8015 - br | 4.95 mm +/- 0.1 |

Print: HUBER+SUHNER RG 142 B/U 50 Ohm (production order number)

Electrical Data

| | |
|--------------------------------|--|
| Impedance | 50 Ω +/- 2 |
| Operating Frequency | 6 GHz |
| Capacitance | 95 pF/m |
| Velocity of signal propagation | 69 % |
| Signal delay | 4.75 ns/m |
| Screening effectiveness | ≥ 85 dB (up to 6 GHz) |
| Operating voltage | ≤ 2.5 kV _{rms} (at sea level) |
| Test voltage | 5 kV _{rms} (50 Hz/1 min) |

Mechanical Data

| | | |
|---------------------|--------|----------------|
| Weight | | 6.4 kg/100 m |
| Min. bending radius | static | 30 mm 50 mm |

Environmental Data

| | |
|--|--------------------|
| Temperature range | -65 °C ... +200 °C |
| Installation temperature | -20 °C... +60 °C |
| Flame propagation test | IEC 60332-3, |
| Halogen free | No |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |
| 1907/2006/EC (REACH) | compliant |

Additional Information

MIL reference: M17/60-RG142 (former reference: M17/158-00001)

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

| | |
|-------------|------------------|
| Cable group | U9 3 mm / 50 Ohm |
|-------------|------------------|

Flexible RF cable

RG_142_B/U Item: 22510037

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.3956

b = 0.0645

$f_{\max} = 6$

P at 1GHz = 407

| Frequency (GHz) | Nom. attenuation (dB / m) sea level 25° C ambient temperature | Nom. attenuation (dB / ft) sea level 25° C ambient temperature | Max. CW power (W) sea level 40° C ambient temperature |
|--------------------|---|--|---|
| 0,3 | 0,24 | 0,072 | 743 |
| 0,6 | 0,35 | 0,105 | 525 |
| 0,9 | 0,43 | 0,132 | 429 |
| 1,2 | 0,51 | 0,156 | 372 |
| 1,5 | 0,58 | 0,177 | 332 |
| 1,8 | 0,65 | 0,197 | 303 |
| 2,1 | 0,71 | 0,216 | 281 |
| 2,4 | 0,77 | 0,234 | 263 |
| 2,7 | 0,82 | 0,251 | 248 |
| 3,0 | 0,88 | 0,268 | 235 |
| 3,3 | 0,93 | 0,284 | 224 |
| 3,6 | 0,98 | 0,300 | 215 |
| 3,9 | 1,03 | 0,315 | 206 |
| 4,2 | 1,08 | 0,330 | 199 |
| 4,5 | 1,13 | 0,344 | 192 |
| 4,8 | 1,18 | 0,359 | 186 |
| 5,1 | 1,22 | 0,373 | 180 |
| 5,4 | 1,27 | 0,386 | 175 |
| 5,7 | 1,31 | 0,400 | 170 |
| 6,0 | 1,36 | 0,413 | 166 |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[RG_142_B/U](#)